

Times Square

WOVEN FABRIC



AC-65500 Berry #1



AC-65501 Amber #2



AC-65503 Herb #4



AC-65504 Midnight #5



AC-65505 Graphite #6



AC-65502 Beach #3

Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance

Environmental

- LBC Red List Free
- OEKO-TEX Standard 100 Certified
- No PFAS, fluorocarbons or perfluorinated compounds
- No added flame retardants
- No added antimicrobials
- Formulated without Phthalates

Cleaning and Maintenance

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications



Content	100% Polyester
Finish	Non-PFAS / Water-Based Stain Resistant
Backing	Acrylic
Weight	25 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Repeat	Horizontal: 14.5 inches, Vertical: 30.0 inches, directional
Roll Size	50 yards

Performance Characteristics

Abrasion Resistance** ASTM D-4157	Exceeds 115,000 double rubs
Break Strength ASTM D-5034	Warp: 319 lbs. min., Fill: 321 lbs. min.
Seam Slippage ASTM D-4034	Warp: 73.5 lbs. min., Fill: 111 lbs. min.
Brush Pilling ASTM D-3511	Class 5.0 min.
Colorfastness to Light AATCC-16	40 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 4.5, Wet: Class 5.0

Flammability*

ASTM E-84 (Unadhered)	Class A or 1
California Technical Bulletin 117-2013 Section 1	Passed
NFPA 260	Class 1
UFAC	Class 1

C.F. Stinson, LLC
2849 Product Drive
Rochester Hills, MI 48309

P 800 841 6279
F 248 299 3884

cfstinson.com