

Name	Engrave
Content	95% Polycarbonate Polyurethane, 5% Silicone Face 100% Polyester Back
Finish	<i>WriteOut</i> Ink Resistant Finish
Width	54 inches Engrave Cannot Be Railroaded
Application	Upholstery
Environmental	Meets criteria for Healthy Hospital Initiative. Does Not Contain: Formaldehyde, PVC, Phthalates, BPA, Antimony, Lead, Heavy Metals, Fire Retardant Chemicals, Antimicrobial/Antibacterial additives, Perfluorinated Compounds.

This Fabric Has Passed:

Flammability	California Bulletin 117-13; UFAC: Class 1/NFPA 260
Abrasion	300,000* Double Rubs (Wyzenbeek Method) *Multiple factors affect fabric durability and appearance retention including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.
Print Retention	ASTM D3389 Class 5
Lightfastness	200 Hours
Hydrolytic Stability	(7 weeks) ISO 1419
Cleaning	WS, Bleach Cleanable using 20% Bleach Maximum/80% Water Solution Cleaning instructions are available at arc-com.com/engrave



Dye lots may vary slightly.

Custom colors are available through our ArcCom Options® Studio.

©2019

arc-com.com
800.223.5466