


RENEW[®]
eco-conscious
Recycled Wall Surfaces

Custom colors are available through
Arc-Com Wall Surfaces Studio.
Minimum yardage requirements apply.


Triad Untrimmed

Triad material shipped untrimmed. Red lines indicate recommended trim line. For best installation double cutting on the wall is recommended.
54" Horizontal Match / 25 1/4" Vertical Repeat
Straight Across Match at 54" / Non-Reverse Hang - 54" finished width.



Triad Trimmed

Triad shown with recommended trim line - 54" finished width. For best installation double cutting on the wall is recommended.



Arc Com

Physical Properties:

Width:	54/55"
Finished Width:	54"
Repeat:	54" Horizontal Match / 25 1/4" Vertical Repeat Straight Across Match at 54" / Non-Reverse Hang
Weight:	Type II, 20 Ounces Per Linear Yard / 626 Grams Per Linear Meter
Backing:	Recycled Non-Woven (10% Post Consumer Recycled Content)
Tear Strength:	34 x 25
Tensile Strength:	89 x 88
Fire Rated:	Class A / ASTM E-84 Tunnel Test NFPA Life Safety Code 101-6-5.3

Flame Spread: 20* Smoke Developed: 15*

Criteria Values on 5/8" Type X Gypsum Board:
Flame Spread: 0-25 / Smoke Developed: 0-450

This test method is also published under the following designations:

ANSI 255	NFPA 255	UBC 42-1	UL 723	CAN/ULC-S-102
----------	----------	----------	--------	---------------

*The numerical flame spread rating referenced herein is not intended to reflect hazards presented by this or any other material under actual fire conditions. Arc-Com shall submit, upon request, a Certificate of Compliance that wallcoverings used meet specifications and modifications outlined herein.

MEA

Acceptance: Approved for use in the City of New York, Department of Buildings.

Federal

Specifications: Meets or exceeds requirements for Type II material for Federal Specifications CCC-W-408 A/C/D and W-101 WA Quality Standard for Polymer Coated Fabric Wallcovering. Tested in accordance with test procedures detailed in Federal Specification CCC-T-191A.

Quality Standards:

Low in VOC's / Printed with water based inks.

California 01350 Indoor Air Quality: Low VOC emitting vinyl wallcoverings meets California Department of Health Services Section 01350 requirements for office and school interiors (LEED® IEQ 4.6).

Stain and Mildew Resistance: Best rating (0) as tested in accordance with G.S.A. Federal Specification CCC-W-408 A/C/D.

Anti-Microbial: All of our vinyl wallcoverings contain bactericide and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.

LEED® Points: 10% Post Consumer Recycled Content contributes to LEED® POINTS (LEED® MR4).

Can contribute to LEED® IEQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives.

Backing made from rapidly renewable materials and wood pulp sourced from managed forests (LEED® MR 6.7).

Performance Features:

Composition: Recycled Material - Contains Post Consumer Recycled Content.
Free of Cadmium, Mercury and ozone-depleting chemicals.

Permeability: Vinyl wallcovering has little or no moisture permeability. If the design, construction or maintenance of a building and / or other circumstances allows moisture to accumulate in a wall or wall cavity, vinyl wallcovering can act as a vapor barrier restricting the escape of moisture and increasing the risk of mold growth. Vinyl wallcovering permeability can be increased through perforation and alternative product constructions with varying degrees of increased permeability depending on methods used. An experienced professional who is familiar with building conditions and circumstances should be consulted concerning benefits and limitations of vinyl wallcovering. Arc-Com Wallcoverings contain additives to resist mold and other micro-biological growth on the product. Those additives, however, will not prevent mold growth if moisture is allowed to accumulate behind the wall.

For more information on wallcovering permeability and mold, Arc-Com recommends that you visit www.wallcoverings.org.

Perforation/ Micro-Venting:

Vinyl wallcovering permeability can be increased through perforation/micro-venting, when installed with permeable wallcovering primer and adhesive. Perforation/Micro-Venting is available on a custom order basis, 30 yard minimum quantity per color, at an additional cost.

Metallics: The environmental lighting of your installation may create a subtle gradation of color due to the light reflective quality of this design utilizing pearlescent and metallic inks.

Natural Materials: The subtle variations exhibited in designs that are replications of natural materials are a natural inherent characteristic and expected beauty of these designs.

Warranty: 5 Year Limited Warranty on Manufacturing Defects.

Installation: 54" Horizontal Match / 25 1/4" Vertical Repeat
Straight Across Match at 54" / Non-Reverse Hang
Detailed Arc-Com installation instructions are enclosed with each bolt.

t.800.223.5466 arc-com.com.com/triad MADE IN USA ©2018