

Recycled Content
Bleach Cleanable

Panel | Acoustic

Theory 3006

Theory 3006

Panel | Acoustic

Specifications

Content	100% pre-consumer recycled polyester
Weight	10.8 ± 1.0 oz./lin. yd
Width	66" min. useable
Repeat	none

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 175 lbf min. warp and 150 lbf min. fill
	Flammability ASTM E84 Class I or A

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:	100%
------------------------	------

For more detailed results, please consult our website.

Miscellaneous

- Application testing of this product is recommended.
 - Colors may vary between dye lots.
 - This is a directional fabric.
- Proudly woven in North America supporting our local communities.**

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

Sustainability

100% recycled and recyclable



	Cotton 040		Citrus 021
	Bisque 033		Spice 020
Marina 050		Camel 032	Chive 030
Pewter 031	Truffle 012	Shadow 010	Lagoon 011