



SOAVE

GENERAL SPECIFICATIONS

Width	54"
Weight	33 oz/linear yard
Roll Size	30 yds
Composition	Facing: 100% PVC Backing: 100% Polyester Suede
Finish	Urethane Topcoat
CAB 2998 Compliant	Yes
Prop 65 Compliant	Yes

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
FMVSS 302	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	150,000+ DR
Cold Crack	-10°
Colorfastness to Crocking	Wet: 4-5 Dry: 4-5
Tensile Strength	Passes
Tear Strength	Passes
Elongation	Passes
Adhesion Coating	Passes
UV Resistance	300 Hours

CLEANING INSTRUCTIONS

To keep Soave looking great, please clean spills as soon as they occur with a mild soap and water solution and a clean cloth. For more difficult stains, lightly wipe the stain with a 60% isopropyl rubbing alcohol, using a dry or damp cloth. Do not rub hard as this may push the stain into the surface. After cleaning, use a clean damp cloth to wipe away the solution residue. Please do not soak the stain with water as this could damage the surface. Allow the area to air dry.

RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR
LIVING



*ACT® Registered Certification Marks