



CATEGORY

Upholstery

PROPERTIES



CONTENT

92% Polyester/6% Polyurethane/2% Silicone

BACKING

Fluid Barrier (Supreen) Polyurethane

FINISH

Supreen (Silicone) - PFC/PFOA Free

WIDTH

54"

WEIGHT

22 oz./linear yard

SHOWN RAILOADED

No

DIRECTIONAL

Yes

ROLL LENGTH

35 yards

VISUAL REPEAT

n/a, n/a

BREAKING STRENGTH

Warp 330/Fill 145

SEAM STRENGTH

Warp: 87.5/Fill: 99.5

ABRASION RESISTANCE

Exceeds 100,000 Double Rubs (Wyzenbeek)

Back: n/a. Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE

Class 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

APPLICATION

Indoor

FLAMMABILITY

Passes Cal 117-2013; NFPA 260/UFAC Class 1

WARRANTY

Standard Upholstery | '5' Five Year Warranty

GREENGUARD
GOLD Certified